

CDF Operations Report

Rob Harr February 2, 2004 All Experimenters Meeting



This Week's Stores

Date	Store	Inst Lum (initial)	Delivered Lum [nb ⁻¹]	Lum to tape nb^{-1} (ϵ)	Comment
Mo 1/26	3195	44.7e30	325	199 (61%)	Vacuum, high losses
Tu 1/27	3197	41.9e30	1925	1658 (86%)	
Th 1/29	3206	33.9e30	1032	896 (87%)	Corr. Elem. trip
Sa 1/31	3210	50.4e30	1577	1203 (76%)	Abort gap losses, trig test
Su 2/1	3212	53.6e30	2595	2265 (87%)	RF failure
Total			7454	6221 (83%)	




Detector Status

- We made use of the Monday and Friday access times:
 - -Silicon investigations and fixes
 - COT readout electronics board
 - -CEM HV
 - -Measured I/V curves for diode dosimeters
 - -Investigated a problem with lighting in the hall
- We redistributed the data input to the event builder to better balance the data load and allow higher rates into level 3.
 - $-275Hz \rightarrow 330Hz$



Abort Gap Losses

- The rate of abort gap losses is monitored for the protection of the silicon detector.
 - -We worry if the rate exceeds 20kHz
 - -At ~15kHz we call the MCR and ask that they try to lower the rates
- For recent stores, the rates begin low (few kHz) but climb steadily.
- Scraping helps -- collimator E03 is usually effective
- Contributes to deadtime
- We are concerned that we understand neither why the losses rise, nor why scraping helps.





Efficiency

- Several improvements have improved our data taking efficiency (especially at high luminosity):
 - -Improvements to our error recovery procedures (rebooting alpha midrun)
 - -Recent upgrade of the Level 3 farm
 - Redistributing the load to the event builder
 - -Modifications to the trigger code
 - -For this morning's store at 58e30, we ran our standard trigger and had 10% deadtime
 - -For the past week, our overall efficiency reached 83%
- More improvements are in development
 - -Level 2 muon code
 - -More efficient DSP code



Summary

- The CDF detector is running well
 - -We are solving the many small problems that effected data taking at the beginning of the year
 - -Data taking efficiency is rising towards above 85%
 - -We welcome the improving Tevatron luminosity